



Compact Display

for displaying velocity

- easy to read 7 segment display
- easy operation
- universal application
- glare protection
- power supply 10 to 30 V
- reverse polarity protection

Typical Technical Specifications

Power supply:	10 ... 30 V; 2 W
Input voltage:	0...10 V; -10 V ... + 10 V
Dimensions (l x w x h):	approx. 112 x 116 x 59 mm
Weight:	approx. 750 g incl. suction cup
Display:	7 segment display 5 digit LED, height 14.2 mm
Display range:	-19999 ... 99999
Operating temperature:	-10°C ... +50°C
Storage temperature:	-25°C ... +70°C
Protection standard:	IP65

Recommendation:

The front side of the display should be cleaned by a soft, moistened cloth only. Please do not use solvents or detergents!



Art. No. 11370

In a continuous effort to improve our products, CORRSYS-DATRON reserves the right to change specifications without prior notice.

©2008 CORRSYS-DATRON Sensorsysteme GmbH / Germany
CompactDisplay_d-215-e-rev001 10/08

CORRSYS-DATRON
www.corrsys-datron.com

International Headquarters
CORRSYS-DATRON Sensorsysteme GmbH
P.O. Box 1349 • 35523 Wetzlar / Germany
Phone: +49-6441-9282-0
Fax: +49-6441-9282-17
e-mail: sales@corrsys-datron.com

North American Headquarters
CORRSYS-DATRON Sensorsystems Inc.
40000 Grand River, Suite 503 • Novi, MI 48375 • USA
Phone: 248-615-2035 • Toll-free: 800-832-0732
Fax: 248-615-2184
e-mail: USA-sales@corrsys-datron.com

Chinese Headquarters
CORRSYS-DATRON Sensorsysteme GmbH - China
Room 610, JinTianDi International Mansion,
No. 998 RenMin Road, Shanghai (200021), P.R.China
Phone: ++86-21-63114144 • Fax: ++86-21-63114154
e-mail: Xiaoying.Li@corrsys-datron.com.cn